



PROFESSIONAL FIRE EXTINGUISHERS

ABC DRY CHEMICAL STORED PRESSURE FIRE EXTINGUISHERS

SUPERIOR QUALITY - MANUFACTURED AND TESTED TO ANSI/UL STANDARDS. AMEREX IS A ISO-9002 REGISTERED FIRM.

RUGGED CONSTRUCTION - EASY AND LESS COSTLY TO MAINTAIN AND SERVICE

ULC & U.S. COAST GUARD LISTED - 6 YEAR WARRANTY

BAR CODED LABELS FOR DOCUMENTING EXTINGUISHER LOCATIONS, INSPECTIONS, MAINTENANCE AND RECHARGING

COMPLETE RANGE OF SIZES FOR ALL HAZARD REQUIREMENTS

TEMPERATURE RANGE: - 65° To + 120° F.



ABC or MULTI-PURPOSE extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F. and coats the surface to which it is applied, it smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

Available in a variety of types and sizes of Wheeled and Stationary extinguishers.

SPECIFICATIONS	ABC Dry Chemical										
VALVES	ALUMINUM						BRASS, CHROME PLATED				
Size & Capacity (lbs.)	2 ½	5	5	6	10 Tall	20	5	6	10 Short	10 Tall	20
Application	Nozzle		Hose and Nozzle				Hose and Nozzle				
Model Number	B417 / B417T	A500 / A500T	A402 / A402T	B443	B456	A411	424	B461	419	B441	423
ULC Rating	1A: 5B:C	3A: 10B:C	3A: 40B:C	3A: 40B:C	6A: 80B:C	10A: 120B:C	2A: 10B:C	3A: 40B:C	6A: 80B:C	4A: 60B:C	10A: 120B:C
Shipping Wt. (lbs.)	5 ¼ / 5 ½	9 ¼ / 9 ½	9 ¼ / 9 ½	12 ¼	18	38	10 ½	13 ¼	19	19	39
Height (in.)	15 ½	15 ¼	15 ¼	16	20	23 ¼	15 ½	16 ¼	17 5/8	20 ½	24
Width (in.)	5 ¼	7 ¼	7 ¼	7 ¼	7 ¼	10 ¼	8	8 ½	9 ½	8 ¼	10 ¼
Depth (Diam. - in.)	3	4 ¼	4 ¼	5	5	7	4 ¼	5	6	5	7
Range (ft.)	9 - 15	12 - 18	12 - 18	15 - 21	15 - 21	15 - 21	12 - 18	15 - 21	15 - 21	15 - 21	15 - 21
Discharge Time (Sec.)	10	14	14	14 ½	20	30	14	14	22	20	30
Available with Chrome Plated Cylinder	✓	✓	✓		✓					✓	
F. M. Approved	✓	✓		✓	✓	✓		✓	✓	✓	✓
Standard Bracket	Wall / Vehicle-Marine			Wall			Wall				

Note: All extinguishers are U.S. Coast Guard approved with the bracket listed on the ULC label.



COMPLIANCE-1 FIRE EXTINGUISHERS

ALUMINUM CYLINDER DRY CHEMICAL FIRE EXTINGUISHERS



MODEL # SF1.25B

MODEL # SF2A

MODEL # SF2.5A110

MODEL # SF5AW

MODEL # SF10A

COMPLIANCE 1

FEATURES

- ✦ Non corrosive pull pin
- ✦ Completely rechargeable
- ✦ Full hand grip for ease of operation
- ✦ Waterproof stainless steel gauge
- ✦ Anodized aluminum valve
- ✦ All aluminum cylinder, no steams, no welds, no rust
- ✦ Most parts are interchangeable
- ✦ Cylinder has high corrosion and impact resistant finish (red apoxy)
- ✦ Individually packaged



WOOD • TRASH • PAPER



LIQUIDS • GREASE



ELECTRICAL EQUIP.



LIQUIDS • GREASE



ELECTRICAL EQUIP.



LISTED

SPECIFICATIONS

	MODEL	DESCRIPTION	RATING	RANGE FT.	DISCHARGE TIME (SECS)	PSI	HEIGHT (INCHES)	WIDTH (INCHES)	DIAMETER (INCHES)	WEIGHT (LB./KG)
ABC	SF1.25B	1 LB BC FIRE EXTINGUISHER	2BC	5-6	8.5-11.5	100	9 3/4	3 3/4	2 7/8	34 / 15.4 (18)
	SF2A	2LB ABC FIRE EXTINGUISHER C./VEH BRACKET	1AB, 5BC	7-9	9.5-11.5	100	12 7/8	3 3/4	2 7/8	39.5 / 17.9(12)
	SF2.5A110	2.5LB ABC FIRE EXTINGUISHER C./VEH BRACKET	1A, 10BC	8-10	12-14	150	15 1/4	3 3/4	3 1/8	4 1/4 / 2.1
	SF5AW	5LB ABC FIRE EXTINGUISHER C./WALL BRACKET	3A, 10BC	8-10	14-16	195	16	6 3/4	4 1/4	8 / 3.6
	SF5AV	5LB ABC FIRE EXTINGUISHER C./VEH BRACKET	3A, 10BC	8-10	14-16	195	16	6 3/4	4 1/4	8 / 3.6
BC	SF10A	10LB ABC FIRE EXTINGUISHER C./WALL BRACKET	6A, 80BC	10-15	20-22	195	21 1/4	8 1/8	5 1/4	17 1/2 / 7.9
	SF2.5B	2.5LB BC FIRE EXTINGUISHER C./VEH BRACKET	5BC	8-10	12-14	150	14	3 3/4	3 1/8	4 1/4 / 2.1
	SF5BW	5LB BC FIRE EXTINGUISHER C./WALL BRACKET	10BC	8-10	14-16	195	16	6 3/4	4 1/4	8 / 3.6
	SF5BV	5LB BC FIRE EXTINGUISHER C./VEH BRACKET	10BC	8-10	14-16	195	16	6 3/4	4 1/4	8 / 3.6
	SF10B	10LB BC FIRE EXTINGUISHER C./WALL BRACKET	60BC	10-15	20-22	195	21 1/4	8 1/8	5 1/4	17 1/2 / 7.9

WARRANTY

Strike First Corporation warrants its fire extinguishers to be free from defects in material and workmanship for a period of six (6) years from the date of purchase. During the warranty period, any such defects will be repaired or the defective extinguisher replaced (If the original seal is intact and/or if only factory replacement parts have been used to service the extinguisher). This warranty does not cover defects resulting from modifications, alteration, misuse, exposure to corrosive conditions or improper installation or maintenance. All implied warranties, including, but not limited to, warranties of fitness for purpose and mer-

chantability, are limited to the time period as stated above. In no event shall Strike First Corporation be liable for incidental or consequential damages. Strike First Corporation neither assumes nor authorizes any representative or other person to assume for it any obligation or liability other than as expressly set forth herein. This warranty gives you specific legal rights, and you may also have other rights which vary from province to province.